

ATTENTION REGULATORY MANAGER

49 CFR § 178.2 (c)(ii) NOTICE

PER 49 CFR § 178.2 (c)(ii), THE BELOW LISTED CLOSURES AND GASKETS WERE USED TO QUALIFY IBCNA'S PASSPORT IBC. YOU MUST USE THE APPROVED GASKET AND CLOSURE TIGHTENED TO THE APPROPRIATE TORQUE TO MEET THE DOT REQUIREMENTS.

BLOW MOLDED 31HA1 CLOSURE DESCRIPTIONS – PER BELOW OR PRINT (PASSPORTS)

LID – 6" HDPE WITH VITON®, SANTOPRENE AND EPDM COMBINE, VITON®, EPDM OR NBR GASKET WITH OR WITHOUT 2" NPT BUNG WITH SANTOPRENE GASKET. TIGHTEN 6" TO 40 FOOT POUNDS USING COMPATIBLE LUBRICANT. TIGHTEN 9" LIDS TO 75 FOOT POUNDS. TIGHTEN 2" TO 30 INCH POUNDS.

BOTTOM DISCHARGE – 2" FLANGE/VALVE/ADAPTER COMBINATION (PP WITH GLASS AND CARBON BLACK; EPDM, VITON®, PE, OR SANTOPRENE O-RINGS, TEFLON® SEATS AND STEM BUSHINGS), 2" DUST CAP (PP WITH GLASS AND CARBON BLACK AND 2" EPDM, VITON®, OR TEFLON® GASKET) AND 2" FLANGE O-RING GASKET (EPDM, VITON® OR TEFLON®). RED HANDLE SANTOPRENE VALVES WITH PLASTIC COLLAR TO BE TIGHTENED TO 45 FOOT POUNDS; 1.5" OR 2" GREY HANDLE (VITON®) AND BLUE HANDLE (EPDM) VALVES WITH PLASTIC COLLAR TO BE TIGHTENED TO 55 FOOT POUNDS; 2" STEEL COLLAR BALL VALVE W/ EPDM OR VITON® GASKET TO BE TIGHTENED TO 55 FOOT POUNDS; AND 2" STEEL COLLAR BALL VALVE WITH SANTOPRENE GASKET TO BE TIGHTENED TO 45 FOOT POUNDS.

REV 2